

DECLARATION OF PERFORMANCE

N. 1101-CPR-18-06

1. Unique identification code of the product-type: **FASSACOUCHE**
2. Intended uses: **One coat rendering mortar for external use (OC)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.com**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2016**

Notified bodies: NA

7. Declared performances:

Reaction to fire	A1
Water absorption	W2
Water permeability after weathering cycles	≤ 1 ml/cm² after 48 h
Water vapor permeability	10
Adhesion	NPD

Adhesion after weathering cycles	≥ 0,2 N/mm²
Thermal conductivity λ	0,43 W/mK (tabulated value)
Durability	See: adhesion after weathering cycles/water permeability test after weathering cycles
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 21/06/2018

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA n° 02015890268



FASSA S.r.l.

ETICHETTA CE

Prodotto: FASSACOUCHE



Fassa s.r.l.

Via Lazzaris, 3
31027 Spresiano (TV) – Italy
15

1101-CPR-18-06

EN 998-1: 2016

FASSACOUCHE

**One coat rendering mortar for external use (OC)
for external use**

Reaction to fire:	A1
Water absorption:	W2
Water permeability after weathering cycles:	≤ 1 ml/cm ² after 48 h
Water vapour permeability:	10
Adhesion:	NPD
Adhesion after weathering cycles:	≥ 0,2 N/mm ²
Thermal conductivity λ:	0,43 W/mK (tabulated value) See: adhesion after weathering
Durability:	cycles/water permeability test after weathering cycles
Dangerous substances:	See MSDS