

DECLARATION OF PERFORMANCE

N. LZ13-CPR-18-011

1. Unique identification code of the product-type: **GYPSOTECH GYPSOLIGNUM ZERO 13**
2. Intended uses: **Gypsum plasterboard in building construction**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabor-
tolo.com**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **3 for the reaction to
fire, 4 for the other characteristics**
6. Harmonised standard: **EN 520:2009**

Notified bodies: **T²I - Trasferimento tecnologico ed innovazione s.c.a.r.l. (n.1600)**

7. Declared performances:

Shear strength - $\uparrow\downarrow$	NPD
Reaction to fire – R2F	A1
Water vapor resistance factor - μ	13
Flexural strength – F	Compliant

Thermal conductivity - λ	0,29 W/mK
Impact resistance - $\rightarrow I$:	See manufacturer's literature
Airborn sound insulation – R	
Acoustic absorption - α	

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 31/011/2018

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
REDAZIONE TEL. 0422 5896268



ETICHETTA CE

Prodotto: GYPSOTECH GYPSOLIGNUM ZERO 13



18

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

LZ13-CPR-18-011

EN 520:2009

DEFH1I-12,5

GYPSOTECH GYPSOLIGNUM ZERO 13

Gypsum plasterboard in building construction

Shear strength - $\uparrow\downarrow$	NPD
Reaction to fire – R2F	A1
Water vapor resistance factor - μ :	13
Flexural strength – F	Compliant
Thermal conductivity - λ	0,29 W/m ² K
Impact resistance - $\rightarrow I$:	See
Airborn sound insulation – R	manufacturer's
Acoustic absorption - α	literature