

Safety Data Sheet

FASSAFILL LARGE

Safety Data Sheet dated 23/01/2024 version 3



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: FASSAFILL LARGE

Trade code: 1227

UFI: GETX-CAUT-V00W-X17M

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Cementitious sealant in powder form

1.3. Details of the supplier of the safety data sheet

Company: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - Italy

Tel. +39 0422 7222

Fax +39 0422 887509

Imported in the UK:

FASSA UK LTD

Ashchurch Business Centre,

Alexandra Way, Ashchurch, Tewkesbury GL20 8TD- UK

Tel. +44 (0) 1684.212272

Responsible: laboratorio.spresiano@fassabortolo.it

1.4. Emergency telephone number

NHS 111

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1 May cause an allergic skin reaction.

STOT SE 3 May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Precautionary statements

P261 Avoid breathing dust.

P280 Wear protective gloves and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.
P501 Dispose of contents/container in accordance with national regulation.

Contains:

Portland cement clinker
2-octyl-2H-isothiazol-3-one

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.
The product has been classified according to Regulation (EC) No 1272/2008 (CLP) as amended by UK CLP Regulation, UK SI 2019/720 and UK SI 2020/1567.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Contains biocide with fungicide and algicide properties for dry films. Active substances: 2-octyl-2H-isothiazol-3-one (CAS 26530-20-1) and terbutryn (CAS 886-50-0). In accordance with art. 58 of Regulation no. 528/2012, this product is defined as a "treated article" (not a biocidal product).

For information on respirable silica crystalline, quartz (respirable fraction), see section 11.

The mixture has a low chromium content. In the ready-to-use formulation, after adding water, the maximum soluble hexavalent chromium content is 2 mg/kg dry weight. To ensure a low chromium content, it is nevertheless essential to store the product correctly, in a dry place and for no longer than the maximum specified shelf life. The percentage of respirable crystalline silica is less than 1%. Identification of the product is not therefore mandatory. Respiratory protective equipment is however recommended.

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: FASSAFILL LARGE

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number:
≥30 - <50 %	Portland cement clinker	CAS:65997-15-1 EC:266-043-4	Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1B, H317; STOT SE 3, H335	Exempted
≥0.5 - <1 %	Silica crystalline, quartz (respirable fraction)	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372	Exempted
≥0.00015 - <0.0015 %	2-octyl-2H-isothiazol-3-one	CAS:26530-20-1 EC:247-761-7 Index:613-112-00-5	Acute Tox. 3, H311 Acute Tox. 3, H301 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Skin Corr. 1, H314 Acute Tox. 2, H330, M-Chronic:100, M-Acute:100, EUH071	
Specific Concentration Limits: C ≥ 0.0015%: Skin Sens. 1A H317				
Acute Toxicity Estimate: ATE - Oral: 125mg/kg bw ATE - Dermal: 311mg/kg bw ATE - Inhalation (Dust/mist): 0.27mg/l				

Refer to section 8.1 for information on the crystalline silica, quartz (respirable fraction)
Classifications according to Regulation (EC) No 1272/2008 (CLP) as amended by UK CLP Regulation, UK SI 2019/720 and UK SI 2020/1567.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:
Remove contaminated clothing immediately and dispose off safely.
Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.
OBTAIN IMMEDIATE MEDICAL ATTENTION.

In case of eyes contact:
After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist

immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

The symptoms and effects are as expected from the hazards as shown in section 2.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2, powder extinguisher, foam, water spray.

Product is not flammable.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

In the event of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Dry vacuuming using suitable equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

After the product has been recovered, rinse the area and materials involved with water.

Retain contaminated washing water and dispose it.

In the event of accidental spillage, remove the product by dry vacuuming.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with the skin and eyes and inhalation of dust.

Avoid operations that cause the spread of dust.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Control of soluble hexavalent chromium:

For cements treated with a hexavalent chromium reducing agent, in accordance with the regulations given in section 15, the effectiveness of the reducing agent diminishes with time. The packaging of the material therefore includes information on the production date and the appropriate storage conditions and period to maintain the activity of the reducing agent and keep the content of soluble hexavalent chromium below 2 ppm of the total dry weight of the cement, in accordance with EN 196-10.

Incompatible materials:
See chapter 10.5

Instructions as regards storage premises:
Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)
See chapter 1.2

Industrial sector specific solutions:
None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Notes
Portland cement clinker CAS: 65997-15-1	ACGIH		1				(E,R), A4 - Pulm func, resp symptoms, asthma
	MAK	AUSTRIA	5.000		10.000		Inhalable aerosol
	VLEP	BELGIUM	1.000				Respirable fraction
	ÁK	HUNGARY	10.000				Inhalable fraction
	NDS	POLAND	6.000				Inhalable fraction
	NDS	POLAND	2.000				Respirable fraction
	VLA	SPAIN	4.000				Respirable fraction
	SUVA	SWITZERLAN D	5.000				Inhalable aerosol
	WEL	U.K.	10.000				Inhalable aerosol
	WEL	U.K.	4.000				Respirable aerosol
	GVI	CROATIA	10.000				Inhalable aerosol
	GVI	CROATIA	4.000				Respirable aerosol
	ACGIH		0.025				(R), A2 - Pulm fibrosis, lung cancer
Silica crystalline, quartz (respirable fraction) CAS: 14808-60-7	EU		0.1				
	MAK	AUSTRIA	0.050				
	VLEP	FRANCE	0.100				Respirable aerosol
	ÁK	HUNGARY	0.150				Respirable aerosol
	NDS	POLAND	0.100				
	VLA	SPAIN	0.050				
	SUVA	SWITZERLAN D	0.150				Respirable aerosol
	MAC	NETHERLAND S	0.075				Respirable dust
	GVI	CROATIA	0.100				
	MV	SLOVENIA	0.150				
	IPRV	LITHUANIA	0.100				
	MAK	AUSTRIA	0.05		0.1		Inhalable aerosol
	AGW	GERMANY	0.050		0.100		Inhalable fraction, Skin
2-octyl-2H-isothiazol-3-one CAS: 26530-20-1	MAK	GERMANY	0.050		0.100		Inhalable fraction, Skin
	SUVA	SWITZERLAN D	0.050		0.100		Inhalable aerosol

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m³; PNOC inhalable fraction: 10 mg/m³). For values above these limits, use a P type filter, with a class (1, 2 or 3) chosen according to the outcome of the risk assessment.

8.2. Exposure controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general

extraction.

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use suitable clothing that provides complete protection to the skin according to activity and exposure (EN 14605/EN 13982), e.g. overall, apron, safety shoes, suitable clothing.

Protection for hands:

There is no material or combination of materials for gloves that can guarantee unlimited resistance to any individual chemical or combination of chemicals.

For prolonged or repeated handling, use chemical resistant gloves.

Suitable materials for safety gloves (EN 374/EN 16523); NBR (Nitril rubber): thickness ≥ 0.4 mm; permeation time ≥ 480 min.;

FKM (Fluorinated rubber): thickness ≥ 0.4 mm; permeation time ≥ 480 min.

The choice of suitable gloves does not only depend on the material, but also on other quality characteristics that vary from one manufacturer to another and on the manner and times according to which the mixture is used.

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

Particle filter device (EN 143): mask with filter P2.

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Environmental exposure controls:

See point 6.2

Hygienic and Technical measures

See section 7.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: Powder

Color: various

Odour: Odourless

Melting point / freezing point: N.D.

Initial boiling point and boiling range: N.D.

Flammability: N.A.

Upper/lower flammability or explosive limits: N.D.

Flash point: N.A.

Auto-ignition temperature: N.D.

Decomposition temperature: N.D.

pH: $\geq 12.00 \leq 13.00$ (50% in water dispersion)

Kinematic viscosity: N.A.

Relative density: 1300-1400 kg/m³ (Internal method)

Vapour density: N.A.

Vapour pressure: N.D.

Solubility in water: partially soluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Particle characteristics:

Based on the available data, the product does not contain nanomaterials.

9.2. Other information

Conductivity: N.A.

Explosive properties: N.D.

Oxidizing properties: N.D.

Evaporation rate: N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Keep this product in a dry place.

10.5. Incompatible materials

None in particular.

See chapter 10.3

10.6. Hazardous decomposition products

None.

No hazardous decomposition products when stored and handled correctly.

See chapter 5.2

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on hazard classes as defined in the retained Regulation (EC) No 1272/2008 (CLP) as amended by UK CLP Regulation, UK SI 2019/720 and UK SI 2020/1567.

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: STOT SE 3(H335)
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Portland cement clinker	a) acute toxicity	LD50 Skin Rabbit > 2000 mg/kg
2-octyl-2H-isothiazol-3-one	a) acute toxicity	ATE - Oral : 125 mg/kg bw
		ATE - Dermal : 311 mg/kg bw
		ATE - Inhalation (Dust/mist) : 0.27 mg/l

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

Information on crystalline silica:

The International Agency for Research on Cancer has declared that crystalline silica inhaled due to occupational exposure may cause lung cancer in humans. It nonetheless underlined that the risk does not pertain to all industrial situations nor all types of crystalline silica. In 2003, the EU Scientific Committee on Occupational Exposure Limit values declared that the main effect on humans is inhalation of respirable crystalline silica dust is silicosis. Sufficient information is available to conclude that the relative risk of lung cancer is higher among persons affected by silicosis. Protection of workers is guaranteed by compliance with current occupational exposure limit values. Workers must also receive suitable training on the appropriate use and handling of the product.

SECTION 12: Ecological information

Adopt good working practices, so that the product is not released into the environment.

12.1. Toxicity

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
2-octyl-2H-isothiazol-3-one	CAS: 26530-20-1 - EINECS: 247-761-7 -	a) Aquatic acute toxicity : LC50 Fish 0.036 mg/l 96h

- a) Aquatic acute toxicity : EC50 Daphnia 0.42 mg/l 48h
a) Aquatic acute toxicity : EC50 Algae 0.084 mg/l 72h
b) Aquatic chronic toxicity : NOEC Fish 0.022 mg/l 28d
b) Aquatic chronic toxicity : NOEC Daphnia 0.002 mg/l 21d
b) Aquatic chronic toxicity : NOEC Algae 0.004 mg/l 72h

12.2. Persistence and degradability

Component	Persistence/Degradability:
2-octyl-2H-isothiazol-3-one	Non-readily biodegradable

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT/vPvB in percentage $\geq 0.1\%$.

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Do not allow it to enter drains or watercourses.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Once the product has expired, it must be disposed of in accordance with current legislation.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

N.A.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A.

Sea (IMDG):

N.A.

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Directive 2010/75/EU

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None.

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

None

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

Class 1: slightly hazardous for water.

SVHC Substances:

On the basis of available data, the product does not contain any SVHC in percentage $\geq 0.1\%$.

In order to provide information to manufacturers and users of products and materials containing crystalline silica, a guide has been created for managing respirable crystalline silica and the safe use of products containing crystalline silica in the workplace. For information: <http://www.nepsi.eu>: Agreement on workers' health protection through the good handling and use of crystalline silica and products containing it (2006/C 279/02).

This product contains a biocide with fungicidal and algicidal properties for film. Active substances: 2-octyl-2H-isothiazol-3-one (CAS 26530-20-1) and terbutryn (CAS 886-50-0). In accordance with art. 58 of Regulation no. 528/2012, this product is defined as a "treated article" (not a biocidal product).

Relevant EU provisions transposed through retained EU legislation:

UK REACH List of restrictions (Annex XVII);

UK REACH Candidate list of substances of very high concern (SVHC) for authorisation;

UK REACH List of substances subject to authorisation (Annex XIV);

Export and import of hazardous chemicals - Prior informed consent (PIC regulation).

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.

Code	Hazard class and hazard category	Description
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1

3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
--	---------------------------------

3.2/2	Calculation method
3.3/1	Calculation method
3.4.2/1	Calculation method
3.8/3	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

Safety data sheets of raw materials suppliers.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DNEL: Derived No Effect Level.

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IC50: half maximal inhibitory concentration

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

N.D.: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TLV-TWA: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 3: Composition/information on ingredients
- SECTION 8: Exposure controls/personal protection
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 15: Regulatory information