

DECLARATION OF PERFORMANCE

N. 1277-CPR-24-03

1. Unique identification code of the product-type: **AQUAZIP FAST**
2. Intended uses: **Coating for intended use in concrete surface protection by protection against ingress, moisture control and increasing resistivity method**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **2+ (3 for the reaction to fire)**
6. Harmonised standard: **EN 1504-2:2004**

Notified bodies: **ICMQ (n.1305)**

TPI - Trasferimento tecnologico ed innovazione s.c.a.r.l. (n. 1600)

7. Declared performances:

Permeability to CO ₂	Sd > 50 m
Water vapour permeability	Class I
Capillary absorption and permeability to water	< 0,1 kg/m²·h^{0,5}
Thermal compatibility after freeze-thaw cycles	≥ 0,8 N/mm²

Thermal compatibility after thunder shower	≥ 0,8 N/mm²
Adhesion strength by pull-off test	≥ 0,8 N/mm²
Reaction to fire	E
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction - Inorganic Products Manager

Spresiano (TV), 05/03/2024

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA 03015890268

AQUAZIP FAST



1305

1600

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

19

1277-CPR-24-03

EN 1504-2:2004

AQUAZIP FAST

**Coating for intended use in concrete surface protection
by protection against ingress, moisture control and
increasing resistivity method**

Permeability to CO₂:	Sd > 50 m
Water vapor permeability:	Class I
Capillary absorption and permeability to water:	< 0,1 kg/m ² ·h ^{0,5}
Thermal compatibility after freeze- thaw cycling:	≥ 0,8 N/mm ²
Thermal compatibility after thunder shower:	≥ 0,8 N/mm ²
Adhesion strength by pull-off test	≥ 0,8 N/mm ²
Reaction to fire:	E
Dangerous substances:	See MSDS