

**DECLARATION OF PERFORMANCE**

**N. 1280-CPR-19-10**

1. Unique identification code of the product-type: **FASSA THERMOBENESSERE**
2. Intended uses: **Thermal insulating mortar (T)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.com**
4. Authorised representative: **Not applicable**
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2016**

Notified bodies: NA

7. Declared performances:

Reaction to fire	<b>C-s1, d0</b>
Water absorption	<b>W1</b>
Water permeability after weathering cycles	<b>NPD</b>
Water vapor permeability	<b>9</b>
Adhesion	<b>NPD</b>

Adhesion after weathering cycles	<b>NPD</b>
Thermal conductivity	<b>T1</b>
Durability	<b>NPD</b>
Dangerous substances	<b>See MSDS</b>

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Dott. Samuele Beraldo**

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 10/10/2019

**FASSA S.r.l.**  
Via Lazzaris n° 3  
31027 SPRESIANO (TV)  
Partita IVA 02015890268



**FASSA S.r.l.**

FASSA THERMOBENESSERE



**Fassa s.r.l.**

Via Lazzaris, 3  
31027 Spresiano (TV) – Italy  
21

**1280-CPR-19-10**

**EN 998-1: 2016**

**FASSA THERMOBENESSERE**

**Thermal insulating mortar (T)  
for internal/external use**

<b>Reaction to fire:</b>	C-s1, d0
<b>Water absorption:</b>	W1
<b>Water permeability after weathering cycles:</b>	NPD
<b>Water vapour permeability:</b>	9
<b>Adhesion:</b>	NPD
<b>Adhesion after weathering cycles:</b>	NPD
<b>Thermal conductivity:</b>	T1
<b>Durability:</b>	NPD
<b>Dangerous substances:</b>	See MSDS

**FASSA S.r.l.**