

DECLARATION OF PERFORMANCE

N. 629-CPR-19-05

1. Unique identification code of the product-type: **MB60**
1. Intended uses: **Designed general purpose masonry mortar for use in elements subject to structural requirements**
2. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
3. Authorised representative: **Not applicable**
4. Systems of Assessment and Verification of Constance of Performance (AVCP): **2+**
5. Harmonised standard: **EN 998-2:2016**

Notified bodies: **ICMQ (n. 1305)**

6. Declared performances:

Compressive strength	M 10
Shear strength	0,15 N/mm² (tabulated value)
Contents of chlorides	NPD
Reaction to fire	A1
Water absorption	< 0,30 kg/(m² x min^{0,5})
Proportion of constituents	NPD

Water vapour permeability	μ 15/35
Thermal conductivity λ	0,82 W/mK Tabulated value: P=50%
Durability	NPD
Dangerous substances	See MSDS
Flexural strenght	NPD

7. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 24/05/2019

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA 02015890268



FASSA S.r.l.

MB60



1305

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

04

629-CPR-19-05

EN 998-2:2016

MB60

**Designed general purpose masonry
mortar for use in elements subject to
structural requirements**

Compressive strength:	M 10
Proportion of constituents	NPD
Initial shear strength:	0,15 N/mm ² (tabulated value)
Flexural strength:	NPD
Contents of chloride:	NPD
Reaction to fire:	A1
Water absorption:	< 0,30 kg/(m ² x min ^{0.5})
Water vapour permeability:	μ 15/35
Thermal conductivity λ:	0,82 W/mK P=50%
Durability:	NPD
Dangerous substances:	See MSDS

FASSA S.r.l.