

DECLARATION OF PERFORMANCE

N. 003-CPR-18-09

1. Unique identification code of the product-type: **FASSATHERM CLASSIC F**
2. Intended uses: **External Thermal Insulation Composite System with rendering for the use as external insulation to the walls of buildings**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **1 for the reaction to fire, 2+ for the other characteristics**
6. European Assessment Document: **ETAG 004 Edition 2013, used as EAD**
European Technical Assessment: **ETA 13/0532**
Technical Assessment Body: **CSTB Centre Scientifique et Technique du Bâtiment**
Notified bodies: **ITC-CNR (n.0970)**
7. Declared performances:

Reaction to fire	B-s2, d0	Bond strenght: base coat onto insulation product	≥ 0,08 MPa or cohesive failure in the insulation product
Water absorption after 24 hours	< 0,5 Kg/m²	Bond strenght: adhesive onto substrate	≥ 0,25 MPa under dry conditions ≥ 0,08 MPa 48 h immersion + 2 h 23°C / 50% RL ≥ 0,25 MPa 48 h immersion + 7 g 23°C / 50% RL
Hygrothermal behaviour	Pass	Bond strenght: adhesive onto insulation product	≥ 0,08 MPa under dry conditions or cohesive failure in the insulation product ≥ 0,03 MPa 48 h immersion + 2 h 23°C / 50% RL or cohesive failure in the insulation product ≥ 0,08 MPa 48 h immersion + 7 g 23°C / 50% RL or cohesive failure in the insulation product
Freeze/thaw behaviour	Pass	Fixing strenght (displacement test)	NPD
Impact resistance	Category I – II-III	Wind load resistance	See ETA 13/0532
Water vapour permeability	≤ 1 m	Bond strenght after ageing	≥ 0,08 MPa or cohesive failure in the insulation product
Thermal resistance	R ≥ 1 m²K/W	Dangerous substances	See MSDS of each product

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager


 FASSA S.r.l.
 Via Lazzaris, n° 3
 31027 SPRESIANO (TV)
 Italy Tel. +39 0422 450268

Spresiano (TV), 17/09/2018

FASSATHERM CLASSIC F



0970

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

13

003-CPR-18-09

ETA 13/0532

FASSATHERM CLASSIC F