DECLARATION OF PERFORMANCE

N. 1275-CPR-20-05

1. Unique identification code of the product-type: **AQUAZIP FLOOR & WALL**
2. Intended uses: **Coating for intended use in concrete surface protection by protection against ingress, moisture control and increasing resistivity method**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **2+**
6. Harmonised standard: **EN 1504-2:2005**

Notified bodies: **ICMQ (n.1305)**

7. Declared performances:

Permeability to CO_2	**Sd > 50 m**
Water vapour permeability	**Class I**
Capillary absorption and permeability to water	**< 0,1 kg/m²·h^{0,5}**
Thermal compatibility after freeze-thaw cycles	**≥ 0,8 N/mm²**

Thermal compatibility after thunder shower	**≥ 0,8 N/mm²**
Adhesion strength by pull-off test	**≥ 0,8 N/mm²**
Reaction to fire	**E**
Dangerous substances	**See MSDS**

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo
Research & Development and Quality Direction - Inorganic Products Manager

Spresiano (TV), 15/05/2020

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)

AQUAZIP FLOOR & WALL

CE

1305

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

19

1275-CPR-20-05

EN 1504-2:2005

AQUAZIP FLOOR & WALL

Coating for intended use in concrete surface protection by protection against ingress, moisture control and increasing resistivity method

Permeability to CO_2:	Sd > 50 m
Water vapor permeability:	Class I
Capillary absorption and permeability to water:	< 0,1 kg/m²·h^{0,5}
Thermal compatibility after freeze-thaw cycling:	≥ 0,8 N/mm²
Thermal compatibility after thunder shower:	≥ 0,8 N/mm²
Adhesion strength by pull-off test	≥ 0,8 N/mm²
Reaction to fire:	E
Dangerous substances:	See MSDS