

DECLARATION OF PERFORMANCE

N. 1305-CPR-21-11

1. Unique identification code of the product-type: **BIO INTONACO DI FONDO**
2. Intended uses: **General purpose rendering/plastering mortar (GP)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.com**
4. Authorised representative: **Not applicable**
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2016**

Notified bodies: NA

7. Declared performances:

Reaction to fire	A1
Water absorption	W0
Water permeability after weathering cycles	NPD
Water vapor permeability	12
Adhesion	≥ 0,2 N/mm² - FP:B

Adhesion after weathering cycles	NPD
Thermal conductivity	λ = 0,55 W/mK (tabulated value)
Durability	NPD
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 16/11/2021

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Tel. +39 0422 7222 - Fax +39 0422 887509
P.IVA 02015890268

FASSA S.r.l.

BIO INTONACO DI FONDO



Fassa s.r.l.

Via Lazzaris, 3
31027 Spresiano (TV) – Italy
21

1305-CPR-21-11

EN 998-1: 2016

BIO INTONACO DI FONDO

**General purpose rendering/plastering mortar (GP)
for internal/external use**

Reaction to fire:	A1
Water absorption:	W0
Water permeability after weathering cycles:	NPD
Water vapour permeability:	12
Adhesion:	$\geq 0,2 \text{ N/mm}^2$ - FP:B
Adhesion after weathering cy- cles:	NPD
Thermal conductivity:	$\lambda = 0,55 \text{ W/mK}$ (tabulated value)
Durability:	NPD
Dangerous substances:	See MSDS

FASSA S.r.l.