

DECLARATION OF PERFORMANCE

N. 1289-CPR-23-06

1. Unique identification code of the product-type: **FASSA BRICKFIX**
2. Intended uses: **Improved deformable cementitious adhesive with reduced slip and extended open time for internal and external tiling**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: **NA**
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **3**
6. Harmonised standard: **EN 12004:2007 + A1:2012**

Notified bodies: **SOCOTEC Italia srl nr. 1308**

T²I - Trasferimento tecnologico ed innovazione s.c.a.r.l. (n. 1600)

7. Declared performances:

Reaction to fire	A2, s1 - d0
Initial tensile adhesion strength	≥ 1.0 N/mm²
Early tensile adhesion strength	NA
Tensile adhesion strength after heat ageing	≥ 1.0 N/mm²

Tensile adhesion strength after water immersion	≥ 1.0 N/mm²
Tensile adhesion strength after freeze/thaw cycles	≥ 1.0 N/mm²
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA n° 02015890268



Spresiano (TV), 28/06/2023

FASSA S.r.l.

FASSA BRICKFIX



1308

1600

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

21

1289-CPR-23-06

EN 12004:2007 + A1:2012

FASSA BRICKFIX

Improved deformable cementitious adhesive with reduced slip and extended open time for internal and external tiling

Reaction to fire:	A2, s1 - d0
Initial tensile adhesion:	≥ 1.0 N/mm ²
Early tensile adhesion:	NA
Tensile adhesion after heat ageing:	≥ 1.0 N/mm ²
Tensile adhesion after water contact:	≥ 1.0 N/mm ²
Tensile adhesion after freeze/thaw cycles:	≥ 1.0 N/mm ²
Dangerous substances:	See MSDS

FASSA S.r.l.