

DECLARATION OF PERFORMANCE

N. 1237-CPR-18-03

1. Unique identification code of the product-type: **FASSAFLOOR ECO**
2. Intended uses: **Calcium sulphate screed material for use internally in buildings**
3. Manufacturer: **FASSA S.r.l. - Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 13813:2002**
Notified bodies: Not applicable
7. Declared performances:

Reaction to fire	A1FL
Release of corrosive substances	CA - pH $\geq$ 7
Water permeability	NPD
Permeability to water vapour	NPD
Compressive strength	C20
Flexural strength	F5

Wear resistance	NPD
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano, 27/03/2018

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
P. IVA 02015890268

FASSA S.r.l.

FASSAFLOOR ECO



Fassa s.r.l.
Via Lazzaris, 3
31027 Spresiano (TV) – Italy
18
1237-CPR-18-03

EN 13813:2002 - CA-C20-F5

FASSAFLOOR ECO
Calcium sulphate screed material for use
internally in buildings

Reaction to fire:	A1FL
Release of corrosive substances:	CA - pH $\geq$ 7
Water permeability:	NPD
Water vapor permability:	NPD
Compressive strength:	C20
Flexural strength:	F5
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance λ:	NPD
Chemical resistance:	NPD

FASSA S.r.l.