DECLARATION OF PERFORMANCE

N. 592-CPR-16-10

1. Unique identification code of the product-type: **RB201**
2. Intended uses: **General purpose rendering/plastering mortar (GP)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.com**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2010**

   Notified bodies: NA

7. Declared performances:

Reaction to fire	**A1**
Water absorption	**W1**
Water permeability after weathering cycles	**NPD**
Water vapor permeability	**14**
Adhesion	**≥ 0,3 N/mm² - FP:B**

Adhesion after weathering cycles	**NPD**
Thermal conductivity λ	**0,53 W/mK (tabulated value)**
Durability	**NPD**
Dangerous substances	**See MSDS**

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo
Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 03/10/2016

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)

ETICHETTA CE

Prodotto: RB201

CE

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

04

592-CPR-16-10

EN 998-1: 2010

RB201

General purpose rendering/plastering mortar (GP)

for external/internal use

Reaction to fire:	A1
Water absorption:	W1
Water permeability after weathering cycles:	NPD
Water vapour permeability:	14
Adhesion:	≥ 0,3 N/mm² - FP:B
Adhesion after weathering cycles:	NPD
Thermal conductivity λ:	0,53 W/mK (tabulated value)
Durability:	NPD
Dangerous substances:	See MSDS