

DECLARATION OF PERFORMANCE

N. 603-CPR-16-10

1. Unique identification code of the product-type: **MV40**
1. Intended uses: **Designed general purpose masonry mortar use in elements subject to structural requirements**
2. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
3. Authorised representative: Not applicable
4. Systems of Assessment and Verification of Constance of Performance (AVCP): **2+**
5. Harmonised standard: **EN 998-2:2010**

Notified bodies: **ICMQ (n. 1305)**

6. Declared performances:

Compressive strength	M 10
Shear strength	0,15 N/mm² (tabulated value)
Contents of chlorides	NPD
Reaction to fire	A1
Water absorption	< 0,30 kg/(m² x min^{0,5})

Water vapour permeability	μ 15/35
Thermal conductivity λ	0,82 W/mK Tabulated value: P=90%
Durability	NPD
Dangerous substances	See MSDS

7. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 03/10/2016

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA n° 015890268



FASSA S.r.l.

ETICHETTA CE

Prodotto: MV40



1305

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

04

603-CPR-16-10

EN 998-2:2010

MV40

**Designed general purpose masonry
mortar use in elements subject to
structural requirements**

Compressive strength:	M 10
Initial shear strength:	0,15 N/mm ² (tabulated value)
Contents of chloride:	NPD
Reaction to fire:	A1
Water absorption:	< 0,30 kg/(m ² x min ^{0.5})
Water vapour permeability:	μ 15/35
Thermal conductivity λ:	0,82 W/mK P=90%
Durability:	NPD
Dangerous substances:	See MSDS