

DECLARATION OF PERFORMANCE

N. 421-CPR-16-10

1. Unique identification code of the product-type: **RSR 421**
2. Intended uses: **Plaster based on organic binder ready to use for external use**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **3 for the reaction to fire, 4 for the other characteristics**
6. Harmonised standard: **EN 15824:2009**

Notified bodies: **Istituto Giordano (n.0407)**

7. Declared performances:

| | |
|------------------------------|----------------------|
| Permeability to water vapour | V₂ |
| Water absorption | W₃ |
| Adhesion | ≥ 0,3 MPa |
| Durability | NPD |

| | |
|----------------------|---|
| Thermal conductivity | 0,74 W/mK (tabulated value, P = 50%) |
| Reaction to fire | A2 - s1,d0 |
| Dangerous substances | See MSDS |
| | |

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Riccardo Scattolin

Research & Development and Quality Direction - Organic Products Manager


Spresiano (TV), 03/10/2016

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA 02015890268



ETICHETTA CE

Prodotto: RSR 421

| | | | | | | | | | | | | | | |
|--|-----------------------------------|----------------|--------------------------|----------------|------------------|-----------|--------------------|-----|------------------------------|-----------|--------------------------|------------|------------------------------|----------|
|  | | | | | | | | | | | | | | |
| Fassa s.r.l. Via Lazzaris, 3 31027 Spresiano (TV) – Italy 11 421-CPR-16-10 | | | | | | | | | | | | | | |
| EN 15824:2009 RSR 421 Plaster based on organic binder ready to use for external use <table><tr><td>Water vapour permeability:</td><td>V₂</td></tr><tr><td>Water absorption:</td><td>W₃</td></tr><tr><td>Adhesion:</td><td>≥ 0,3 MPa</td></tr><tr><td>Durability:</td><td>NPD</td></tr><tr><td>Thermal conductivity:</td><td>0,74 W/mK</td></tr><tr><td>Reaction to fire:</td><td>A2 - s1,d0</td></tr><tr><td>Dangerous substances:</td><td>See MSDS</td></tr></table> | Water vapour permeability: | V ₂ | Water absorption: | W ₃ | Adhesion: | ≥ 0,3 MPa | Durability: | NPD | Thermal conductivity: | 0,74 W/mK | Reaction to fire: | A2 - s1,d0 | Dangerous substances: | See MSDS |
| Water vapour permeability: | V ₂ | | | | | | | | | | | | | |
| Water absorption: | W ₃ | | | | | | | | | | | | | |
| Adhesion: | ≥ 0,3 MPa | | | | | | | | | | | | | |
| Durability: | NPD | | | | | | | | | | | | | |
| Thermal conductivity: | 0,74 W/mK | | | | | | | | | | | | | |
| Reaction to fire: | A2 - s1,d0 | | | | | | | | | | | | | |
| Dangerous substances: | See MSDS | | | | | | | | | | | | | |