

**DECLARATION OF PERFORMANCE**

**N. 421-CPR-19-02**

1. Unique identification code of the product-type: **RSR 421**
2. Intended uses: **Plaster based on organic binder ready to use for external use**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – [www.fassabortolo.it](http://www.fassabortolo.it)**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **3 for the reaction to fire, 4 for the other characteristics**
6. Harmonised standard: **EN 15824:2017**

Notified bodies: **Istituto Giordano (n.0407)**

7. Declared performances:

|                              |                      |
|------------------------------|----------------------|
| Permeability to water vapour | <b>V<sub>2</sub></b> |
| Water absorption             | <b>W<sub>3</sub></b> |
| Adhesion                     | <b>≥ 0,3 MPa</b>     |
| Durability                   | <b>NPD</b>           |

|                      |   |
|----------------------|---|
| Thermal conductivity | <b>0,74 W/mK<br/>(tabulated value, P = 50%)</b> |
| Reaction to fire     | <b>A2 - s1,d0</b>                               |
| Dangerous substances | <b>See MSDS</b>                                 |

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Dott. Riccardo Scattolin**

Research & Development and Quality Direction - Organic Products Manager

Spresiano (TV), 18/02/2019

**FASSA S.r.l.**  
Via Lazzaris n° 3  
31027 SPRESIANO (TV)  
Partita IVA 02015890268



RSR 421



**Fassa s.r.l.**  
Via Lazzaris, 3  
31027 Spresiano (TV) – Italy  
11  
**421-CPR-19-02**

**EN 15824:2017**

**RSR 421**

**Plaster based on organic binder ready to use for  
external use**

|                                   |                |
|-----------------------------------|----------------|
| <b>Water vapour permeability:</b> | V <sub>2</sub> |
| <b>Water absorption:</b>          | W <sub>3</sub> |
| <b>Adhesion:</b>                  | ≥ 0,3 MPa      |
| <b>Durability:</b>                | NPD            |
| <b>Thermal conductivity:</b>      | 0,74 W/mK      |
| <b>Reaction to fire:</b>          | A2 - s1,d0     |
| <b>Dangerous substances:</b>      | See MSDS       |