

DECLARATION OF PERFORMANCE

N.647 -CPR-16-10

1. Unique identification code of the product-type: **A64 R-Evolution**
2. Intended uses: **Product for non-structural repair of concrete by PCC mortars (hydraulic mortars modified by the addition of polymer additives)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 1504-3:2006**

Notified bodies: Not applicable

7. Declared performances:

Compressive strength	R2
Chloride Ion content	≤ 0,05 %
Adhesive Bond	≥ 0,8 MPa
Thermal compatibility	≥ 0,8 MPa

Capillary Absorption	≤ 0,5 kg x m⁻² x h^{-0,5}
Fire reaction	A1
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 03/10/2016

FASSA S.r.l.
Via Lazzaris, n° 3
31027 SPRESIANO (TV)
Partita IVA 02015890268



ETICHETTA CE

Prodotto: A64 R-Evolution



Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

15

647-CPR-16-10

EN 1504-3:2006

A64 R-Evolution

Product for non-structural repair of concrete by PCC mortars (hydraulic mortars modified by the addition of polymer additives)

Compressive strength:	R2
Contents of chloride:	$\leq 0,05 \%$
Adhesion:	$\geq 0,8 \text{ MPa}$
Thermal compatibility:	$\geq 0,8 \text{ MPa}$
Capillary absorption:	$\leq 0,5 \text{ kg x m}^{-2} \text{ x h}^{-0,5}$
Reaction to fire:	A1
Dangerous substances:	See MSDS