# Safety Data Sheet C 285 BETON-E

Safety Data Sheet dated 12/09/2024 version 4



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Trade name: C 285 BETON-E

Trade code: COLCBE UFI: JF13-P0T1-400M-934D

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Protective elastomer finish for concrete

1.3. Details of the supplier of the safety data sheet

Company: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - Italy

Tel. +39 0422 7222 Fax +39 0422 887509 Imported in the UK: FASSA UK LTD

Ashchurch Business Centre,

Alexandra Way, Ashchurch, Tewkesbury GL20 8TD- UK

Tel. +44 (0) 1684.212272

Responsable: laboratorio.spresiano@fassabortolo.it

## 1.4. Emergency telephone number

NHS 111

#### **SECTION 2: Hazards identification**



# 2.1. Classification of the substance or mixture

# Regulation (EC) n. 1272/2008 (CLP)

Skin Sens. 1 May cause an allergic skin reaction.

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects. Adverse physicochemical, human health and environmental effects:

No other hazards

## 2.2. Label elements

# Regulation (EC) No 1272/2008 (CLP):

## Hazard pictograms and Signal Word



#### **Hazard statements**

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing fume/gas/mist/vapours/spray.

P280 Wear protective gloves/clothing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P501 Dispose of contents/container in accordance with applicable regulations.

# **Special Provisions:**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

 Date
 13/09/2024
 Production Name
 C 285 BETON-E
 Page n. 1 of 14

## **Contains:**

2-octyl-2H-isothiazol-3-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

2-methylisothiazol-3(2H)-one

1,2-benzisothiazol-3(2H)-one

## Special provisions according to Annex XVII of REACH and subsequent amendments:

None

The product has been classified according to Regulation (EC) No 1272/2008 (CLP) as amended by UK CLP Regulation, UK SI 2019/720 and UK SI 2020/1567.

#### 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >=0.1%.

Contains biocide with fungicide and algicide properties for dry films. Active substances: 2-octyl-2H-isothiazol-3-one (CAS 26530-20-1), pyrithione zinc (CAS 13463-41-7), terbutryn (CAS 886-50-0). In accordance with art. 58 of Regulation no. 528/2012, this product is defined as a "treated article" (not a biocidal product).

No other hazards

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

NΔ

## 3.2. Mixtures

Mixture identification: C 285 BETON-E

# Hazardous components within the meaning of the CLP regulation and related classification:

| Qty                               | Name   | Ident. Numb.   | Classification   | Registration Number:  |
|-----------------------------------|--|--|--|-----------------------|
| ≥10 - <20 %                       | titanium dioxide                                       | CAS:13463-67-7<br>EC:236-675-5<br>Index:022-006-<br>00-2 | ' Carc. 2, H351  | 01-2119489379-17-xxxx |
| ≥0.1 - <0.3 %                     | Silica crystalline, cristobalite (respirable fraction) | CAS:14464-46-1<br>EC:238-455-4                           | . STOT RE 1, H372  |                       |
| ≥0.05 - <0.1 %                    | Silica crystalline, quartz (respirable fraction)       | CAS:14808-60-7<br>EC:238-878-4                           | ' STOT RE 1, H372  | Exempted              |
| ≥0.025 - <0.05<br>%               | 2-(2-butoxyethoxy)ethanol                              | CAS:112-34-5<br>EC:203-961-6<br>Index:603-096-<br>00-8   | Eye Irrit. 2, H319   | 01-2119475104-44-xxxx |
| ≥0.0036 -<br><0.036 %             | 1,2-benzisothiazol-3(2H)-one                           | EC:220-120-9   | Acute Tox. 2, H330 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:1, M-Acute:1             |                       |
|                                   |  |  | Specific Concentration Limits: $C \ge 0.036\%$ : Skin Sens. 1A H317  |                       |
|                                   |  |  | Acute Toxicity Estimate:<br>ATE - Oral: 450mg/kg bw<br>ATE - Inhalation (Dust/mist):<br>0.21mg/l   |                       |
| ≥0.005 - <0.025 pyrithione zinc % |  | EC:236-671-3   | Acute Tox. 2, H330 Acute Tox. 3,<br>H301 Eye Dam. 1, H318 STOT RE<br>1, H372 Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 Repr. 1B,<br>H360D, M-Chronic:10, M-<br>Acute:1000 |                       |
|                                   |  |  | Acute Toxicity Estimate:<br>ATE - Oral: 221mg/kg bw<br>ATE - Inhalation (Dust/mist):<br>0.14mg/l   |                       |

Date 13/09/2024 Production Name C 285 BETON-E Page n. 2 of 14

≥0.005 - <0.025 Terbutryn ≥0.0015 -2-octyl-2H-isothiazol-3-one < 0.005 %

CAS:886-50-0 EC:212-950-5

Acute Tox. 4, H302 Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:100, M-Acute:100

Specific Concentration Limits: C ≥ 3%: Skin Sens. 1B H317

Acute Toxicity Estimate: ATE - Oral: 500mg/kg bw

EC:247-761-7 00-5

CAS:26530-20-1 Acute Tox. 3, H311 Acute Tox. 3, H301 Eye Dam. 1, H318 Aquatic Index:613-112- Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Skin Corr. 1, H314 Acute Tox. 2, H330, M-Chronic:100, M-Acute:100, EUH071

> Specific Concentration Limits: C ≥ 0.0015%: Skin Sens. 1A H317

Acute Toxicity Estimate: ATE - Oral: 125mg/kg bw ATE - Dermal: 311mg/kg bw ATE - Inhalation (Dust/mist): 0.27mg/l

>0.00015 -<0.0015 % reaction mass of 5-chloro-2methyl-2H-isothiazol-3-one and 2- Index:613-167- H330 Acute Tox. 3, H301 Skin methyl-2H-isothiazol-3-one (3:1) 00-5

CAS:55965-84-9 Acute Tox. 2, H310 Acute Tox. 2, Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:100, M-Acute:100, EUH071

> Specific Concentration Limits:  $0.6\% \le C < 100\%$ : Skin Corr. 1C H314  $0.06\% \le C < 0.6\%$ : Skin Irrit. 2 H315  $0.6\% \le C < 100\%$ : Eye Dam. 1 H318  $0.06\% \le C < 0.6\%$ : Eye Irrit. 2 H319  $0.0015\% \le C < 100\%$ : Skin Sens. 1A H317

Acute Toxicity Estimate: ATE - Oral: 66mg/kg bw ATE - Dermal: 141mg/kg bw ATE - Inhalation (Dust/mist): 0.17mg/l

≥0.00015 -<0.0015 %

2-methylisothiazol-3(2H)-one

CAS:2682-20-4 EC:220-239-6 Index:613-326-00-9

Acute Tox. 2, H330 Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:1, M-Acute:10, EUH071

Specific Concentration Limits:  $0.0015\% \le C < 100\%$ : Skin Sens. 1A H317

Acute Toxicity Estimate: ATE - Oral: 120mg/kg bw ATE - Dermal: 300mg/kg bw ATE - Inhalation (Dust/mist): 0.134mg/l

The mixture contains >= 1% titanium dioxide CAS 13463-67-7 [in powder form containing >= 1 % of particles with aerodynamic diameter <= 10 µm]. Substance is classified as a category 2 inhalation carcinogenic (H351 inhalation) - Notes V, W, 10. According to Regulation (EC) no. 1272/2008 (CLP), Annex II, part 2, section 2.12, the label on the packaging of liquid mixtures containing >= 1 % titanium dioxide particles with an aerodynamic diameter equal to or below 10 µm shall bear the following statement: EUH211: "Warning! Hazardous

13/09/2024 C 285 BETON-E Date Production Name Page n. 3 of Classifications according to Regulation (EC) No 1272/2008 (CLP) as amended by UK CLP Regulation, UK SI 2019/720 and UK SI 2020/1567.

#### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

In case of skin contact:

Remove contaminated clothing immediatley and dispose off safely.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

#### 4.2. Most important symptoms and effects, both acute and delayed

The symptoms and effects are as expected from the hazards as shown in section 2.

#### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media:

Product is not flammable.

Extinguishing media which must not be used for safety reasons:

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

In the event of fire and/or explosion do not breathe fumes.

#### 5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

## For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

#### For emergency responders:

Wear personal protection equipment.

# 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3. Methods and material for containment and cleaning up

Material suitable for collection: inert absorbent material (e.g. sand, vermiculite)

After the product has been recovered, rinse the area and materials involved with water.

Retain contaminated washing water and dispose it.

#### 6.4. Reference to other sections

See also section 8 and 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

## Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Date 13/09/2024 Production Name C 285 BETON-E Page n. 4 of 14

## 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a cool, well-ventilated place, away from heat.

Keep away from food, drink and feed.

Incompatible materials:

See chapter 10.5

Instructions as regards storage premises:

Adequately ventilated premises.

Protect from frost.

# 7.3. Specific end use(s)

Recommendation(s)

See chapter 1.2

Industrial sector specific solutions:

None in particular

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Community Occupational Exposure Limits (OEL)**

titanium dioxide

CAS: 13463-67-7 OEL Type ACGIH Long Term: 0.2 mg/m3

Notes: Nanoscale particles - A3 - rspr bt, pnmc

Long Term: 2.5 mg/m3

Notes: Finescale particles - A3 - rspr bt, pnmc

OEL Type MAK GERMANY Long Term: 0.3 mg/m3; Short Term: 2.4 mg/m3

Notes: Respirable fraction, except ultrafine particles, Multiplied by the material density

OEL Type VLEP BELGIUM Long Term: 10 mg/m3
OEL Type VLEP FRANCE Long Term: 10 mg/m3

OEL Type VLEP ROMANIA Long Term: 10 mg/m3; Short Term: 15 mg/m3

OEL Type VLA SPAIN Long Term: 10 mg/m3 Notes: Inhalable fraction

OEL Type SUVA SWITZERLAN Long Term: 3 mg/m3 D Notes: Respirable aerosol

D Notes. Respirable delosor

OEL Type WEL U.K. Long Term: 10 mg/m3 Notes: Inhalable aerosol

Long Term: 4 mg/m3

Notes: Respirable aerosol

OEL Type GVI CROATIA Long Term: 10 mg/m3

Notes: Inhalable fraction

Long Term: 4 mg/m3 Notes: Respirable fraction

OEL Type AGW GERMANY Long Term: 1.25 mg/m3

Notes: Respirable dust particles

OEL Type NDS POLAND Long Term: 10 mg/m3

Notes: Inhalable fraction

Silica crystalline, cristobalite (respirable fraction)

CAS: 14464-46-1 OEL Type ACGIH Long Term: 0.025 mg/m3

Notes: (R), A2 - Pulm fibrosis, lung cancer

OEL Type EU Long Term: 0.1 mg/m3

Silica crystalline, quartz (respirable fraction)

CAS: 14808-60-7 OEL Type ACGIH Long Term: 0.025 mg/m3

Notes: (R), A2 - Pulm fibrosis, lung cancer

OEL Type EU Long Term: 0.1 mg/m3
OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3
OEL Type VLEP FRANCE Long Term: 0.1 mg/m3

Notes: Respirable aerosol

Date 13/09/2024 Production Name C 285 BETON-E Page n. 5 of 14

| OEL Type   |                              | OEL Type     | VLA        | SPAIN           | Long Term: 0.05 mg/m3  |
|--|------------------------------|--------------|------------|-----------------|--|
| Notes: Respirable aerosol   Notes: Respirable dust   Notes: Respirable aerosol   Notes: R |                              | OEL Type     | ,          |                 |  |
| OEL Type   |                              | OLL Type     | AK         | HONGARI         | 5  |
| OEL Type   |                              | OEL Type     | MAC        |                 |  |
| OEL Type   |                              | OEL Type     | SUVA       |                 |  |
|  |                              | OEL Type     | GVI        | CROATIA         | Long Term: 0.1 mg/m3   |
|  |                              | OEL Type     | NDS        | POLAND          | Long Term: 0.1 mg/m3   |
| 2-(2-butoxyethox |                              | OEL Type     | MV         | SLOVENIA        | Long Term: 0.15 mg/m3  |
| CAS: 112-34-5         OEL Type         ACGIH         Long Term: 10 ppm Notes: (IPV) - Hematologic, liver and kidney eff           CAS: 112-34-5         OEL Type         EU         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         MAK         AUSTRIA         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLEP         BELGIUM         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.5 mg/m3 - 15 ppm           OEL Type         VLEP         FRANCE         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLEP         FRANCE         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLEP         FRANCE         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLEP         ROMANIA         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLE         SPAIN         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLE         PORTUGAL         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLE         VLE         LONG         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLE         VLE         VLE         <  |                              | OEL Type     | IPRV       | LITHUANIA       | Long Term: 0.1 mg/m3   |
| CAS: 112-34-5         OEL Type         ACGIH         Long Term: 10 ppm Notes: (IPV) - Hematologic, liver and kidney eff           CAS: 112-34-5         OEL Type         EU         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         MAK         AUSTRIA         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLEP         BELGIUM         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.5 mg/m3 - 15 ppm           OEL Type         VLEP         FRANCE         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLEP         FRANCE         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLEP         FRANCE         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLEP         ROMANIA         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLE         SPAIN         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLE         PORTUGAL         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLE         VLE         LONG         Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm           OEL Type         VLE         VLE         VLE         <  | 2-(2-butoxyethoxy            | )ethanol     |            |                 |  |
| OEL Type   |                              |              | ACGIH      |                 |  |
| OEL Type   |                              | OEL Type     | EU         |                 | Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm |
| OEL Type   |                              | OEL Type     | MAK        | AUSTRIA         | Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm |
| OEL Type   |                              |              | MAK        | GERMANY         | Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm   |
| OEL Type   |                              |              | VLEP       | BELGIUM         |  |
| OEL Type   |                              |              |            |                 |  |
| OEL Type   |                              |              |            |                 |  |
| OEL Type   |                              |              |            |                 |  |
| OEL Type AK HUNGARY Long Term: 67.5 mg/m3; Short Term: 101.2 mg/m3  OEL Type MAC NETHERLAND Long Term: 50 mg/m3; Short Term: 100 mg/m3  OEL Type VLE PORTUGAL Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  OEL Type SUVA SWITZERLAN Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  OEL Type WEL U.K. Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  OEL Type GVI CROATIA Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  OEL Type AGW GERMANY Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  OEL Type NDS POLAND Long Term: 67 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  OEL Type MV SLOVENIA Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm  OEL Type MV SLOVENIA Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm  OEL Type MAK AUSTRIA Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3; Short Term: 10 mg/m3  Notes: Inhalable aerosol  OEL Type AGW GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3  Notes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3  Notes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  OEL Type MAK GERMANY Long Term: 0.5 mg/m3  Notes: Inhalable fraction   |                              |              |            |                 |  |
| OEL Type   |                              |              |            |                 |  |
| OEL Type   |                              |              |            |                 |  |
| OEL Type   WEL   U.K.   Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101 mg/m3 - 15 ppm   OEL Type   WEL   U.K.   Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm   OEL Type   GVI   CROATIA   Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm   OEL Type   AGW   GERMANY   Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm   OEL Type   NDS   POLAND   Long Term: 67 mg/m3; Short Term: 100 mg/m3   OEL Type   MV   SLOVENIA   Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm   OEL Type   MAK   AUSTRIA   Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm   OEL Type   MAK   AUSTRIA   Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3   Notes: Inhalable aerosol   Notes: Inhalable aerosol   OEL Type   AGW   GERMANY   Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3   Notes: Inhalable fraction, Skin   Notes: Inhalable fraction, Skin   OEL Type   MAK   AUSTRIA   Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3   Notes: Inhalable fraction, Skin   Notes: Inhalable fraction, Skin   OEL Type   MAK   AUSTRIA   Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3   Notes: Inhalable fraction, Skin   OEL Type   MAK   AUSTRIA   Long Term: 0.05 mg/m3; Short Term: 0.4 mg/m3   Notes: Inhalable fraction, Skin   OEL Type   MAK   SERMANY   Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3   Notes: Inhalable fraction   Notes: Inhalable fraction   OEL Type   MAK   SERMANY   Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3   Notes: Inhalable fraction   N |                              | 011.770      |            |                 | 201g 101111 00 11g, 110, 011010 101111 200 111g, 1110            |
| D  OEL Type WEL U.K. Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm OEL Type GVI CROATIA Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm OEL Type AGW GERMANY Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm OEL Type NDS POLAND Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm OEL Type NDS POLAND Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm OEL Type MAK SLOVENIA Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  2-octyl-2H-isothiazol-3-one CAS: 26530-20-1 OEL Type MAK GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable aerosol OEL Type SUVA SWITZERLAN Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  OEL Type AGW GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type SUVA SWITZERLAN Long Term: 0.05 mg/m3 Notes: Inhalable fraction OEL Type SUVA SWITZERLAN Long Term: 0.05 mg/m3 Notes: Inhalable fraction OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 Notes: Inhalable fraction OEL Type SUVA SWITZERLAN Long Term: 0.05 mg/m3 Notes: Inhalable fraction OEL Type MAK AUSTRIA Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction OEL Type MAK AUSTRIA Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction OEL Type MAK AUSTRIA Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction OEL Type MAK AUSTRIA Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  |                              | OEL Type     | VLE        | PORTUGAL        | Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm |
| OEL Type GVI CROATIA Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm OEL Type AGW GERMANY Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm OEL Type NDS POLAND Long Term: 67 mg/m3; Short Term: 100 mg/m3 OEL Type MV SLOVENIA Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm  2-octyl-2H-isothiazol-3-one CAS: 26530-20-1 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable aerosol  OEL Type SUVA SWITZERLAN Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.5 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction   |                              | OEL Type     | SUVA       |                 | Long Term: 67 mg/m3 - 10 ppm; Short Term: 101 mg/m3 - 15 ppm     |
| OEL Type   AGW   GERMANY   Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm  |                              | OEL Type     | WEL        | U.K.            | Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm |
| OEL Type   NDS   POLAND   Long Term: 67 mg/m3; Short Term: 100 mg/m3   |                              | OEL Type     | GVI        | CROATIA         | Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm |
| OEL Type   NDS   POLAND   Long Term: 67 mg/m3; Short Term: 100 mg/m3   |                              | OEL Type     | AGW        | GERMANY         | Long Term: 67 mg/m3 - 10 ppm; Short Term: 100.5 mg/m3 - 15 ppm   |
| 2-octyl-2H-isothiazol-3-one  CAS: 26530-20-1   |                              |              | NDS        |                 |  |
| 2-octyl-2H-isothiazol-3-one  CAS: 26530-20-1   |                              | OEL Type     | MV         | SLOVENIA        | Long Term: 67.5 mg/m3 - 10 ppm; Short Term: 101.2 mg/m3 - 15 ppm |
| CAS: 26530-20-1 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable aerosol  OEL Type MAK GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  OEL Type SUVA SWITZERLAN Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable aerosol  OEL Type AGW GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.05 mg/m3  | 2-octyl-2H-isothiaz          | rol-3-one    |            |                 |  |
| Notes: Inhalable aerosol  OEL Type MAK GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  OEL Type SUVA SWITZERLAN Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable aerosol  OEL Type AGW GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.05 mg/m3  |                              |              | ΜΔΚ        | ΔΙΙςΤΡΙΔ        | Long Term: 0.05 mg/m3: Short Term: 0.1 mg/m3                     |
| Notes: Inhalable fraction, Skin  OEL Type SUVA SWITZERLAN Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable aerosol  OEL Type AGW GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.05 mg/m3; Short Term: 0.4 mg/m3   | CA3. 20330 20 1              | OLL TYPE     | PIZIX      | AOSTICIA        | Notes: Inhalable aerosol   |
| D Notes: Inhalable aerosol  OEL Type AGW GERMANY Long Term: 0.05 mg/m3; Short Term: 0.1 mg/m3 Notes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  |                              | OEL Type     | MAK        | GERMANY         |  |
| Rotes: Inhalable fraction, Skin  reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  CAS: 55965-84-9 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3  OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3  OEL Type MAK GERMANY Long Term: 0.05 mg/m3  |                              | OEL Type     | SUVA       | _               |  |
| CAS: 55965-84-9  OEL Type  MAK  OEL Type  MAK  GERMANY  Long Term: 0.05 mg/m3  Notes: Inhalable fraction  OEL Type  SUVA  SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4  OEL Type  MAK  AUSTRIA  Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  CAS: 2682-20-4  OEL Type  MAK  AUSTRIA  Long Term: 0.05 mg/m3  OEL Type  MAK  GERMANY  Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  |                              | OEL Type     | AGW        | GERMANY         |  |
| CAS: 55965-84-9  OEL Type  MAK  OEL Type  MAK  GERMANY  Long Term: 0.05 mg/m3  Notes: Inhalable fraction  OEL Type  SUVA  SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4  OEL Type  MAK  AUSTRIA  Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  Notes: Inhalable fraction  CAS: 2682-20-4  OEL Type  MAK  AUSTRIA  Long Term: 0.05 mg/m3  OEL Type  MAK  GERMANY  Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  | reaction mass of 5           | -chloro-2-me | ethvl-2H-i | isothiazol-3-on | e and 2-methyl-2H-isothiazol-3-one (3:1)                         |
| OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 Notes: Inhalable fraction  OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 D Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3   |                              |              |            |                 |  |
| Notes: Inhalable fraction  OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3 D Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3  |                              | OEL Type     | MAK        | GERMANY         | Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3                      |
| D Notes: Inhalable fraction  2-methylisothiazol-3(2H)-one  CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3  OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3   |                              |              |            |                 | Notes: Inhalable fraction  |
| CAS: 2682-20-4 OEL Type MAK AUSTRIA Long Term: 0.05 mg/m3 OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3   |                              | OEL Type     | SUVA       |                 |  |
| OEL Type MAK GERMANY Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3   | 2-methylisothiazol-3(2H)-one |              |            |                 |  |
|  | CAS: 2682-20-4               | OEL Type     | MAK        | AUSTRIA         | Long Term: 0.05 mg/m3  |
|  |                              | OEL Type     | MAK        | GERMANY         |  |

 Date
 13/09/2024
 Production Name
 C 285 BETON-E
 Page n. 6 of 14

OEL Type SUVA SWITZERLAN Long Term: 0.2 mg/m3; Short Term: 0.4 mg/m3

D Notes: Inhalable fraction

# **Predicted No Effect Concentration (PNEC) values**

2-(2-butoxyethoxy)ethanol

CAS: 112-34-5 Exposure Route: Fresh Water; PNEC Limit: 1.1 mg/l

Exposure Route: Marine water; PNEC Limit: 0.11 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 4.4 mg/kg

Exposure Route: Marine water; PNEC Limit: 0.44 mg/kg

Exposure Route: Soil; PNEC Limit: 0.32 mg/kg

## **Derived No Effect Level (DNEL) values**

2-(2-butoxyethoxy)ethanol

CAS: 112-34-5 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Professional: 67.5 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects

Worker Professional: 101.2 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 6.25 mg/kg

#### 8.2. Exposure controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.

Eye protection:

Eye glasses with side protection (EN 166).

Protection for skin:

Use suitable clothing that provides complete protection to the skin according to activity and exposure (EN 14605/EN 13982), e.g. overall, apron, safety shoes, suitable clothing.

Protection for hands:

There is no material or combination of materials for gloves that can guarantee unlimited resistance to any individual chemical or combination of chemicals.

For prolonged or repeated handling, use chemical resistant gloves.

Suitable materials for safety gloves (EN 374/EN 16523); NBR (Nitril rubber): thickness >= 0.4 mm; permeation time >= 480 min. Butyl caoutchouc (butyl rubber): thickness >= 0.4 mm; permeation time >= 480 min

The choice of suitable gloves does not only depend on the material, but also on other quality characteristics that vary from one manufacturer to another and on the manner and times according to which the mixture is used.

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

Combination filtering device (EN 14387): mask with filter A-P2.

Environmental exposure controls:

See point 6.2

Hygienic and Technical measures

See section 7.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical State: Liquid Appearance: thick liquid

Color: various

Odour: Characteristic

Melting point/freezing point: N.D.

Boiling point or initial boiling point and boiling range: N.D.

Flammability: N.A.

Lower and upper explosion limit: N.D.

Flash point: > 93°C

Auto-ignition temperature: N.D.

Decomposition temperature: N.D.

pH: >=8.00<=9.00 (Internal method)

Kinematic viscosity:  $> 20.5 \text{ mm}^2/\text{s}$  (40 °C) Density and/or relative density:  $1.20 \div 1.40 \text{ kg/l}$  (Internal method)

Relative vapour density: N.A. Vapour pressure: N.D.

Date 13/09/2024 Production Name C 285 BETON-E Page n. 7 of 14

Solubility in water: miscible in all ratio Solubility in oil: No data available

Partition coefficient n-octanol/water (log value): N.A.

**Particle characteristics:** 

Particle size: N.A. **9.2. Other information** 

Explosive properties: N.A. (Internal assessment) Oxidizing properties: N.A. (Internal assessment)

Evaporation rate: N.A.

Conductivity: N.D.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Stable under normal conditions

#### 10.3. Possibility of hazardous reactions

None

## 10.4. Conditions to avoid

Keep away from heat sources.

#### 10.5. Incompatible materials

None in particular.

#### 10.6. Hazardous decomposition products

No hazardous decomposition products when stored and handled correctly.

See chapter 5.2

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on hazard classes as defined in the retained Regulation (EC) No 1272/2008 (CLP) as amended by UK CLP Regulation, UK SI 2019/720 and UK SI 2020/1567.

# **Toxicological Information of the Preparation**

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation The product is classified: Skin Sens. 1(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

# Toxicological information on main components of the mixture:

titanium dioxide

CAS: 13463-67-7 a) acute toxicity LD50 Oral Rat > 5000 mg/kg

LC50 Inhalation Dust Rat > 6.82 mg/l 4h

2-(2-butoxyethoxy)ethanol

CAS: 112-34-5 a) acute toxicity LD50 Oral Mouse 2410 mg/kg

LC50 Inhalation Vapour Rat > 29 ppm 2h

Date 13/09/2024 Production Name C 285 BETON-E Page n. 8 of 14

1,2-benzisothiazol-3(2H)-one

CAS: 2634-33-5 a) acute toxicity ATE - Oral: 450 mg/kg bw

ATE - Inhalation (Dust/mist): 0.21 mg/l

pyrithione zinc

CAS: 13463-41-7 a) acute toxicity ATE - Oral: 221 mg/kg bw

ATE - Inhalation (Dust/mist): 0.14 mg/l

Terbutryn

CAS: 886-50-0 a) acute toxicity ATE - Oral: 500 mg/kg bw

2-octyl-2H-isothiazol-3-one

CAS: 26530-20-1 a) acute toxicity ATE - Oral: 125 mg/kg bw
ATE - Dermal: 311 mg/kg bw

ATE - Inhalation (Dust/mist): 0.27 mg/l

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

CAS: 55965-84-9 a) acute toxicity ATE - Oral: 66 mg/kg bw

ATE - Dermal: 141 mg/kg bw

ATE - Inhalation (Dust/mist): 0.17 mg/l

2-methylisothiazol-3(2H)-one

CAS: 2682-20-4 a) acute toxicity ATE - Oral: 120 mg/kg bw

ATE - Dermal: 300 mg/kg bw

ATE - Inhalation (Dust/mist): 0.134 mg/l

#### 11.2 Information on other hazards

## **Endocrine disrupting properties:**

No endocrine disruptor substances present in concentration >= 0.1%

#### **SECTION 12: Ecological information**

Adopt good working practices, so that the product is not released into the environment.

### 12.1. Toxicity

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

# List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

### List of Eco-Toxicological properties of the components

titanium dioxide

CAS: 13463-67-7 a) Aquatic acute toxicity: LC50 Fish > 1000 mg/l 96h

a) Aquatic acute toxicity: EC50 Daphnia > 1000 mg/l 48h

a) Aquatic acute toxicity: EC50 Algae 61 mg/l 72h

2-(2-butoxyethoxy)ethanol

CAS: 112-34-5 a) Aquatic acute toxicity: LC50 Fish 1300 mg/l 96h

a) Aquatic acute toxicity: EC50 Daphnia > 100 mg/l 48h

a) Aquatic acute toxicity: EC50 Algae > 100 mg/l 96h

1,2-benzisothiazol-3(2H)-one

CAS: 2634-33-5 a) Aquatic acute toxicity: LC50 Fish 2.2 mg/l 96h

a) Aquatic acute toxicity: EC50 Daphnia 3.27 mg/l 48h a) Aquatic acute toxicity: EC50 Algae 0.11 mg/l 72h

b) Aquatic chronic toxicity: NOEC Fish 0.21 mg/l - 28d

b) Aquatic chronic toxicity: NOEC Daphnia 1.2 mg/l - 21d

b) Aquatic chronic toxicity: NOEC Algae 0.04 mg/l 72h

pyrithione zinc

CAS: 13463-41-7 a) Aquatic acute toxicity: LC50 Fish 0.0104 mg/l 96h

a) Aquatic acute toxicity: EC50 Daphnia 0.051 mg/l 48h a) Aquatic acute toxicity: EC50 Algae 0.0013 mg/l 72h

Date 13/09/2024 Production Name C 285 BETON-E Page n. 9 of 14

```
a) Aquatic acute toxicity: EC50 Freshwater algae 0.051 mg/l 72h
```

b) Aquatic chronic toxicity: NOEC Fish 0.00125 mg/l 28d

b) Aquatic chronic toxicity: NOEC Daphnia 0.0022 mg/l 21d

b) Aquatic chronic toxicity: NOEC Algae 0.00046 mg/l 96h

b) Aquatic chronic toxicity: NOEC Freshwater algae 0.0149 mg/l 72h

## Terbutryn

CAS: 886-50-0 a) Aquatic acute toxicity: LC50 Fish 1.9 mg/l 96h

a) Aquatic acute toxicity: EC50 Algae 6.7 µg/l 72h

a) Aquatic acute toxicity: EC50 Daphnia 6.4 mg/l 48h

b) Aquatic chronic toxicity: NOEC Daphnia 0.05 mg/l 21d

b) Aquatic chronic toxicity: NOEC Fish 0.073 mg/l 28d

b) Aquatic chronic toxicity: NOEC Algae 0.0005 mg/l 72h

### 2-octyl-2H-isothiazol-3-one

CAS: 26530-20-1 a) Aquatic acute toxicity: LC50 Fish 0.036 mg/l 96h

a) Aquatic acute toxicity: EC50 Daphnia 0.42 mg/l 48h

a) Aquatic acute toxicity: EC50 Algae 0.084 mg/l 72h

b) Aquatic chronic toxicity: NOEC Fish 0.022 mg/l 28d

b) Aquatic chronic toxicity: NOEC Daphnia 0.002 mg/l 21d

b) Aquatic chronic toxicity: NOEC Algae 0.004 mg/l 72h

#### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

CAS: 55965-84-9 a) Aquatic acute toxicity: LC50 Fish 0.22 mg/l 96h

a) Aquatic acute toxicity: EC50 Daphnia 0.1 mg/l 48h

a) Aquatic acute toxicity: EC50 Algae 0.0052 mg/l 48h

a) Aquatic acute toxicity: EC50 Freshwater algae 0.048 mg/l 72h

b) Aquatic chronic toxicity: NOEC Fish 0.098 mg/l - 28d

b) Aquatic chronic toxicity: NOEC Daphnia 0.004 mg/l - 21d

b) Aquatic chronic toxicity: NOEC Algae 0.00064 mg/l 48h

b) Aquatic chronic toxicity: NOEC Freshwater algae 0.0012 mg/l 72h

## 2-methylisothiazol-3(2H)-one

CAS: 2682-20-4 a) Aquatic acute toxicity: LC50 Fish 6 mg/l 96h

a) Aquatic acute toxicity: EC50 Daphnia 1.68 mg/l 48h

a) Aquatic acute toxicity: EC50 Algae 0.157 mg/l 72h

b) Aquatic chronic toxicity: NOEC Fish 2.1 mg/l - 28d

b) Aquatic chronic toxicity: NOEC Daphnia 0.55 mg/l  $\,$  -  $\,$  21d

b) Aquatic chronic toxicity: NOEC Algae 0.03 mg/l 72h

## 12.2. Persistence and degradability

2-(2-butoxyethoxy)ethanol

CAS: 112-34-5 Readily biodegradable

 $1, 2\hbox{-benzisothiazol-}3(2H)\hbox{-one}\\$ 

CAS: 2634-33-5 Non-readily biodegradable

pyrithione zinc

CAS: 13463-41-7 Readily biodegradable

2-octyl-2H-isothiazol-3-one

CAS: 26530-20-1 Non-readily biodegradable

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

CAS: 55965-84-9 Non-readily biodegradable

2-methylisothiazol-3(2H)-one

CAS: 2682-20-4 Readily biodegradable

# 12.3. Bioaccumulative potential

N.A.

Date 13/09/2024 Production Name C 285 BETON-E Page n. 10 of 14

# 12.4. Mobility in soil

NΑ

## 12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

## 12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

#### 12.7 Other adverse effects

N.A.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Do not allow it to enter drains or watercourses.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Once the product has expired, it must be disposed of in accordance with current legislation.

#### **SECTION 14: Transport information**

Not classified as dangerous in the meaning of transport regulations.

#### 14.1. UN number or ID number

N/A

# 14.2. UN proper shipping name

ADR-Shipping Name: N/A IATA-Shipping Name: N/A IMDG-Shipping Name: N/A

# 14.3. Transport hazard class(es)

ADR-Class: N/A
IATA-Class: N/A
IMDG-Class: N/A

## 14.4. Packing group

ADR-Packing Group: N/A IATA-Packing group: N/A IMDG-Packing group: N/A

## 14.5. Environmental hazards

Marine pollutant: No Environmental Pollutant: No

IMDG-EMS: N/A

### 14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR exempt: ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code):

# Air (IATA):

IATA-Passenger Aircraft: N/A IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisions: N/A

#### Sea (IMDG):

IMDG-Stowage and handling: N/A

IMDG-Segregation: N/A
IMDG-Subsidiary hazards: N/A
IMDG-Special Provisions: N/A

# 14.7. Maritime transport in bulk according to IMO instruments

N.A.

# **SECTION 15: Regulatory information**

Date 13/09/2024 Production Name C 285 BETON-E Page n. 11 of 14

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Directive 2010/75/EU

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2023/1434 (ATP 19 CLP)

Regulation (EU) n. 2023/1435 (ATP 20 CLP)

Regulation (EU) n. 2024/197 (ATP 21 CLP)

# Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 30, 55, 75

# Provisions related to directive EU 2012/18 (Seveso III):

None

# Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

#### German Water Hazard Class.

Class 2: hazardous for water.

## SVHC Substances:

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  0.1%.

#### VOC content limit value (Directive 2004/42/EC) Category A/c, WB: max. VOC 40 g/l; VOC in product <40 g/l

Contains biocide with fungicide and algicide properties for dry films. Active substances: 2-octyl-2H-isothiazol-3-one (CAS 26530-20-1), pyrithione zinc (CAS 13463-41-7), terbutryn (CAS 886-50-0). In accordance with art. 58 of Regulation no. 528/2012, this product is defined as a "treated article" (not a biocidal product).

Relevant EU provisions transposed through retained EU legislation:

UK REACH List of restrictions (Annex XVII);

UK REACH Candidate list of substances of very high concern (SVHC) for authorisation;

UK REACK List of substances subject to authorisation (Annex XIV);

Export and import of hazardous chemicals - Prior informed consent (PIC regulation).

# 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

# **SECTION 16: Other information**

| Code   | Description                         |
|--------|-------------------------------------|
| EUH071 | Corrosive to the respiratory tract. |
| H301   | Toxic if swallowed.                 |
| H302   | Harmful if swallowed.               |
| H310   | Fatal in contact with skin.         |
| H311   | Toxic in contact with skin.         |
| _      |                                     |

Date 13/09/2024 Production Name C 285 BETON-E Page n. 12 of 14

| H317         | May cause an allergic skin reaction.                                       |   |  |  |  |
|--------------|--|---|--|--|--|
| H318         | Causes serious eye damage.   |   |  |  |  |
| H319         | Causes serious eye irritation.   |   |  |  |  |
| H330         | Fatal if inhaled.  |   |  |  |  |
| H351         | Suspected of causing cancer if inhaled.                                    |   |  |  |  |
| H372         | Causes damage to organs through prolonged or repeated exposure.            |   |  |  |  |
| H372         | Causes damage to organs through prolonged or repeated exposure if inhaled. |   |  |  |  |
| H400         | Very toxic to aquatic life.  |   |  |  |  |
| H410         | Very toxic to aquatic life with long lasting effects.                      |   |  |  |  |
| H412         | Harmful to aquatic life with long lasting effects.                         |   |  |  |  |
| Code         | Hazard class and hazard category   | Description   |  |  |  |
| 3.1/2/Dermal | Acute Tox. 2   | Acute toxicity (dermal), Category 2                               |  |  |  |
| 3.1/2/Inhal  | Acute Tox. 2   | Acute toxicity (inhalation), Category 2                           |  |  |  |
| 3.1/3/Dermal | Acute Tox. 3   | Acute toxicity (dermal), Category 3                               |  |  |  |
| 3.1/3/Oral   | Acute Tox. 3   | Acute toxicity (oral), Category 3                                 |  |  |  |
| 3.1/4/Oral   | Acute Tox. 4   | Acute toxicity (oral), Category 4                                 |  |  |  |
| 3.2/1        | Skin Corr. 1   | Skin corrosion, Category 1  |  |  |  |
| 3.2/1B       | Skin Corr. 1B  | Skin corrosion, Category 1B                                       |  |  |  |
| 3.2/1C       | Skin Corr. 1C  | Skin corrosion, Category 1C                                       |  |  |  |
| 3.2/2        | Skin Irrit. 2  | Skin irritation, Category 2                                       |  |  |  |
| 3.3/1        | Eye Dam. 1   | Serious eye damage, Category 1                                    |  |  |  |
| 3.3/2        | Eye Irrit. 2   | Eye irritation, Category 2  |  |  |  |
| 3.4.2/1      | Skin Sens. 1   | Skin Sensitisation, Category 1                                    |  |  |  |
| 3.4.2/1A     | Skin Sens. 1A  | Skin Sensitisation, Category 1A                                   |  |  |  |
| 3.6/2        | Carc. 2  | Carcinogenicity, Category 2                                       |  |  |  |
| 3.9/1        | STOT RE 1  | Specific target organ toxicity — repeated exposure, Category 1 $$ |  |  |  |
| 4.1/A1       | Aquatic Acute 1  | Acute aquatic hazard, category 1                                  |  |  |  |
| 4.1/C1       | Aquatic Chronic 1  | Chronic (long term) aquatic hazard, category 1                    |  |  |  |
|              |  |   |  |  |  |

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Chronic (long term) aquatic hazard, category 3

# Classification according to Regulation Classification procedure (EC) Nr. 1272/2008

Skin Sens. 1, H317 Calculation method
Aquatic Chronic 3, H412 Calculation method

Causes severe skin burns and eye damage.

Causes skin irritation.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

4.1/C3

H314

H315

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

Safety data sheets of raw materials suppliers.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Aquatic Chronic 3

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BEI: Biological Exposure Index

 ${\it CAS: Chemical \ Abstracts \ Service \ (division \ of \ the \ American \ Chemical \ Society).}$ 

CAV: Poison Center CE: European Community

CLP: Classification, Labeling, Packaging.

Date 13/09/2024 Production Name C 285 BETON-E Page n. 13 of 14

CMR: Carcinogenic, Mutagenic and Reprotoxic

COV: Volatile Organic Compound CSA: Chemical Safety Assessment CSR: Chemical Safety Report

DNEL: Derived No Effect Level.

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IC50: half maximal inhibitory concentration

 ${\tt IMDG: International\ Maritime\ Code\ for\ Dangerous\ Goods.}$ 

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

N.D.: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

**PSG: Passengers** 

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TLV-TWA: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

# Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 6: Accidental release measures
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Date 13/09/2024 Production Name C 285 BETON-E Page n. 14 of 14