

DECLARATION OF PERFORMANCE

N. 710-CPR-18-02

1. Unique identification code of the product-type: **AL88**
2. Intended uses: **General purpose rendering/plastering mortar (GP)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.com**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2016**

Notified bodies: NA

7. Declared performances:

Reaction to fire	A2-s1,d0
Water absorption	W2
Water permeability after weathering cycles	NPD
Water vapor permeability	19
Adhesion	≥ 0,3 N/mm² - FP:B

Adhesion after weathering cycles	NPD
Thermal conductivity λ	0,31 W/mK (tabulated value)
Durability	NPD
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 23/02/2018

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA n° 015890268



FASSA S.r.l.

ETICHETTA CE

Prodotto: AL88



Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

05

710-CPR-18-02

EN 998-1: 2016

AL88

**General purpose rendering/plastering mortar (GP)
for external/internal use**

Reaction to fire:	A2-s1,d0
Water absorption:	W2
Water permeability after weathering cycles:	NPD
Water vapour permeability:	19
Adhesion:	≥ 0,3 N/mm ² - FP:B
Adhesion after weathering cycles:	NPD
Thermal conductivity λ:	0,31 W/mK (tabulated value)
Durability:	NPD
Dangerous substances:	See MSDS