

DECLARATION OF PERFORMANCE

N. AZ13-CPR-16-10

1. Unique identification code of the product-type: **GYPSOTECH STD ZERO BA13**
2. Intended uses: **Gypsum plasterboard in building construction**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY –
www.fassabortolo.com**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 520:2009**

Notified bodies: **NA**

7. Declared performances:

Shear strength - $\uparrow\downarrow$	NPD
Reaction to fire – R2F	A1
Water vapor resistance factor - μ	10
Flexural strength – F	Compliant

Thermal conductivity - λ	0,23 W/mK
Impact resistance - $\rightarrow I$:	See manufacturer's literature
Airborn sound insulation – R	
Acoustic absorption - α	

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 03/10/2016

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA 03015890268



ETICHETTA CE

Prodotto: GYPSOTECH STD ZERO BA13



09

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

AZ13-CPR-16-10

EN 520:2009

A-12,5

GYPSOTECH STD ZERO BA13

Gypsum plasterboard in building construction

Shear strength - $\uparrow\downarrow$	NPD
Reaction to fire – R2F	A1
Water vapor resistance factor - μ :	10
Flexural strength – F	Compliant
Thermal conductivity - λ	0,23 W/m ² K
Impact resistance - $\rightarrow I$:	See
Airborn sound insulation – R	manufacturer's
Acoustic absorption - α	literature

DECLARATION OF PERFORMANCE

N. AZ15-CPR-16-10

1. Unique identification code of the product-type: **GYPSOTECH STD ZERO BA15**
2. Intended uses: **Gypsum plasterboard in building construction**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.com**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 520:2009**

Notified bodies: **NA**

7. Declared performances:

Shear strength - $\uparrow\downarrow$	NPD
Reaction to fire – R2F	A1
Water vapor resistance factor - μ	10
Flexural strength – F	Compliant

Thermal conductivity - λ	0,23 W/mK
Impact resistance - $\rightarrow I$:	See manufacturer's literature
Airborn sound insulation – R	
Acoustic absorption - α	

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 03/10/2016

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA 03015890268



ETICHETTA CE

Prodotto: GYPSOTECH STD ZERO BA15



09

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

AZ15-CPR-16-10

EN 520:2009

A-15

GYPSOTECH STD ZERO BA15

Gypsum plasterboard in building construction

Shear strength - $\uparrow\downarrow$	NPD
Reaction to fire – R2F	A1
Water vapor resistance factor - μ :	10
Flexural strength – F	Compliant
Thermal conductivity - λ	0,23 W/m ² K
Impact resistance - $\rightarrow I$:	See
Airborn sound insulation – R	manufacturer's
Acoustic absorption - α	literature