DECLARATION OF PERFORMANCE

N. 1216-CPR-26-10

1. Unique identification code of the product-type: **NOVANTICA LISCIO**
2. Intended uses: **General purpose rendering/plastering mortar (GP)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.com**
4. Authorised representative: **Not applicable**
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2016**

   Notified bodies:

7. Declared performances:

Reaction to fire	**A1**
Water absorption	**W2**
Water permeability after weathering cycles	**NPD**
Water vapor permeability	**8**
Adhesion	**≥ 0,4 N/mm² - FP:B**

Adhesion after weathering cycles	**NPD**
Thermal conductivity	**λ = 0,34 W/mK (tabulated value)**
Durability	**NPD**
Dangerous substances	**See MSDS**

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo
Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 19/10/2026

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)

NOVANTICA LISCIO

CE

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

26

1216-CPR-26-10

EN 998-1: 2016

NOVANTICA LISCIO

General purpose rendering/plastering mortar (GP)

for external/internal use

Reaction to fire:	A1
Water absorption:	W2
Water permeability after weathering cycles:	NPD
Water vapour permeability:	8
Adhesion:	≥ 0,4 N/mm² - FP:B
Adhesion after weathering cycles:	NPD
Thermal conductivity:	λ = 0,34 W/mK (tabulated value)
Durability:	NPD
Dangerous substances:	See MSDS