**DECLARATION OF PERFORMANCE**

**N. 818-CPR- 16-10**

1. Unique identification code of the product-type: **AQUAZIP RDY**
2. Intended uses: **Dispersion liquid-applied, water impermeable product (DM O1)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **3**
6. Harmonised standard: **EN 14891:2012**

   Notified bodies: **Modena Centro Prove (n. 1599)**

7. Declared performances:

| | |
|---|---|
| Initial tensile adhesion | **≥ 0,5 N/mm²** |
| Water impermeability | **No penetration** |
| Crack bridging ability | **≥ 0,75 mm a 23°C**<br>**≥ 0,75 mm a -5°C** |
| Tensile adhesion after heat ageing | **≥ 0,5 N/mm²** |

| | |
|---|---|
| Tensile adhesion after water contact | **≥ 0,5 N/mm²** |
| Tensile adhesion after contact with lime water | **≥ 0,5 N/mm²** |
| Tensile adhesion after freeze/thaw cycles | **≥ 0,5 N/mm²** |
| Dangerous substances | **See MSDS** |
| | |

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Dott. Samuele Beraldo**
Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 03/10/2016

ETICHETTA CE

Prodotto: AQUAZIP RDY

CE

15

**Fassa s.r.l.**

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

**818-CPR-16-10**

**EN 14891:2012**

**AQUAZIP RDY**

**Dispersion liquid-applied, water impermeable product (DM O1)**

| | |
|---|---|
| **Initial tensile adhesion:** | ≥ 0,5 N/mm² |
| **Water impermeability:** | No penetration |
| **Crack bridging ability:** | ≥ 0,75 mm a 23°C<br>≥ 0,75 mm a -5°C |
| **Initial tensile adhesion after heat ageing:** | ≥ 0,5 N/mm² |
| **Initial tensile adhesion after water contact:** | ≥ 0,5 N/mm² |
| **Initial tensile adhesion after contact with lime water:** | ≥ 0,5 N/mm² |
| **Initial tensile adhesion after freeze/thaw cycles:** | ≥ 0,5 N/mm² |
| **Dangerous substances:** | See MSDS |