DECLARATION OF PERFORMANCE

N. 690-CPR-18-03

1. Unique identification code of the product-type: **SA500**
2. Intended uses: **Cementitious screed material for use internally in buildings**
3. Manufacturer: **FASSA S.r.l. - Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 13813:2002**
   Notified bodies: Not applicable
7. Declared performances:

Reaction to fire	**A1FL**
Release of corrosive substances	**CT**
Water permeability	**NPD**
Permeability to water vapour	**NPD**
Compressive strength	**C20**
Flexural strength	**F5**

Wear resistance	**NPD**
Sound insulation	**NPD**
Sound absorption	**NPD**
Thermal resistance	**NPD**
Chemical resistance	**NPD**

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo
Research & Development and Quality Direction – Inorganic Products Manager

Spresiano, 27/03/2018

ETICHETTA CE

Prodotto: SA500

CE

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

04

690-CPR-18-03

EN 13813:2002 - CT-C20-F5

SA500

Cementitious screed material for use internally in buildings

Reaction to fire:	A1FL
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapor permability:	NPD
Compressive strength:	C20
Flexural strength:	F5
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance λ:	NPD
Chemical resistance:	NPD